


■ SCHWERES GEWINDEROHR GESCHWEISST VERZINKT

EN10255-HEAVY/EN10240-A1


| Zoll | mm | mm | Länge mtr | kg/mtr | GTIN | Zoll | mm | mm | Länge mtr | kg/mtr | GTIN |
|------|------|------|--------------|--------|---------------|-------|------|------|--------------|--------|---------------|
| 1/2 | 21,3 | 3,20 | 6 | 1,520 | 4062768047389 | 1 1/4 | 42,4 | 4,00 | 6 | 4,010 | 4062768047419 |
| 3/4 | 26,9 | 3,20 | 6 | 1,990 | 4062768047396 | 1 1/2 | 48,3 | 4,00 | 6 | 4,630 | 4062768047426 |
| 1 | 33,7 | 4,00 | 6 | 3,100 | 4062768047402 | 2 | 60,3 | 4,50 | 6 | 6,450 | 4062768047433 |



■ GEWINDEROHR NAHTLOS VERZINKT

EN10255-MEDIUM/EN10240-A1


| Zoll | mm | mm | Länge mtr | kg/mtr | GTIN | Zoll | mm | mm | Länge mtr | kg/mtr | GTIN |
|------|------|------|--------------|--------|---------------|-------|------|------|--------------|--------|---------------|
| 1/2 | 21,3 | 2,60 | 6 | 1,270 | 4062768047198 | 1 1/4 | 42,4 | 3,20 | 6 | 3,280 | 4062768047228 |
| 3/4 | 26,9 | 2,60 | 6 | 1,650 | 4062768047204 | 1 1/2 | 48,3 | 3,20 | 6 | 3,770 | 4062768047235 |
| 1 | 33,7 | 3,20 | 6 | 2,550 | 4062768047211 | 2 | 60,3 | 3,60 | 6 | 5,330 | 4062768047242 |



■ GELÄNDERROHR GESCHWEISST SCHWARZ S235 JRH

EN10219


| Zoll | mm | mm | Länge mtr | kg/mtr | GTIN | Zoll | mm | mm | Länge mtr | kg/mtr | GTIN |
|-------|------|------|--------------|--------|---------------|-------|------|------|--------------|--------|---------------|
| 1/2 | 21,3 | 1,75 | 6 | 0,840 | 4062768047891 | 1 1/2 | 48,3 | 2,00 | 6 | 2,280 | 4062768047938 |
| 3/4 | 26,9 | 1,75 | 6 | 1,090 | 4062768047907 | 2 | 60,3 | 2,00 | 6 | 2,880 | 4062768047945 |
| 1 | 33,7 | 2,00 | 6 | 1,560 | 4062768047914 | 2 1/2 | 76,1 | 2,00 | 6 | 3,650 | 4062768047952 |
| 1 1/4 | 42,4 | 2,00 | 6 | 1,990 | 4062768047921 | | | | | | |



■ GELÄNDERROHR GESCHWEISST S235 JRH VERZINKT

EN10219 / EN-ISO1461


| Zoll | mm | mm | Länge mtr | kg/mtr | GTIN | Zoll | mm | mm | Länge mtr | kg/mtr | GTIN |
|-------|------|------|--------------|--------|---------------|-------|------|-----|--------------|--------|---------------|
| 1/2 | 21,3 | 1,75 | 6 | 0,880 | 4062768047969 | 1 1/2 | 48,3 | 2,0 | 6 | 2,390 | 4062768048003 |
| 3/4 | 26,9 | 1,75 | 6 | 1,150 | 4062768047976 | 1 1/2 | 48,3 | 2,0 | 7 | 2,390 | 4062768048072 |
| 1 | 33,7 | 2,0 | 6 | 1,640 | 4062768047983 | 1 1/2 | 48,3 | 2,0 | 7,5 | 2,390 | 4062768048126 |
| 1 | 33,7 | 2,0 | 7 | 1,640 | 4062768048058 | 2 | 60,3 | 2,0 | 6 | 3,020 | 4062768048010 |
| 1 | 33,7 | 2,0 | 7,5 | 1,640 | 4062768048102 | 2 | 60,3 | 2,0 | 7 | 3,020 | 4062768048089 |
| 1 1/4 | 42,4 | 2,0 | 6 | 2,090 | 4062768047990 | 2 | 60,3 | 2,0 | 7,5 | 3,020 | 4062768048133 |
| 1 1/4 | 42,4 | 2,0 | 7 | 2,090 | 4062768048065 | 2 1/2 | 76,1 | 2,0 | 6 | 3,870 | 4062768048027 |
| 1 1/4 | 42,4 | 2,0 | 7,5 | 2,090 | 4062768048119 | | | | | | |



■ KONSTRUKTIONSROHR GESCHWEISST S235 VERZINKT

EN10219/EN-ISO 1461

| mm | mm | mm | Länge mtr | kg/mtr | GTIN | mm | mm | mm | Länge mtr | kg/mtr | GTIN |
|-----|------|------|--------------|--------|---------------|-------|------|------|--------------|--------|---------------|
| 1/2 | 21,3 | 2,00 | 6 | 0,997 | 4062768047839 | 1 1/4 | 42,4 | 2,50 | 6 | 2,583 | 4062768047860 |
| 3/4 | 26,9 | 2,00 | 6 | 1,290 | 4062768047846 | 1 1/2 | 48,3 | 2,50 | 6 | 2,961 | 4062768047877 |
| 1 | 33,7 | 2,50 | 6 | 2,016 | 4062768047853 | 2 | 60,3 | 2,50 | 6 | 3,738 | 4062768047884 |



Wir erweitern ständig unser Lagerprogramm, nicht aufgeführte Abmessungen sind auf Anfrage lieferbar.